




900 Bradley Hill Road, Blauvelt, New York 10913 (845) 353-3300 FAX: (845) 353-3376

TECHNICAL DATA SHEET

**TRI-LAM®
LP-217**

Description: 0.0005" Clear Polyester Film (2.) Permanently Bonded To Tri-Seal Three-ply Co-extruded F-217 (1.)



SPECIFICATIONS

Product	Density lb/ft3	Density g/cc
LP-217	27+/-2	0.43 +/- 0.03
LP -217-36	36+/-2	0.58+/-0.03
LP -219	19+/-2	0.30+/-0.03

Available Web Width		
Minimum [in/mm]	Maximum [in/mm]	Deviation [in/mm]
1" / 25.4mm	19" / 483 mm	+/- 1/16" / 1.6mm

Code of Federal Regulations Compliance: Complies to the following CFR's

- 21CFR177.1520 Olefin polymers.
- 21CFR177.1210 Closures with sealing gaskets for food containers.
- 21CFR178.2010 Antioxidants and or stabilizers for polymers.
- 21CFR175.300 Resinous and polymeric coatings.
- 21CFR 177.1630 Polyethylene Naphthalate Polymers.

**Revised Date: 06/13/01
Revision Number:1**

FDA Status: The component materials of Tri-Lam LP-217, LP-217-36, LP-219 are listed under DMF 2434.

The aforementioned technical information and any recommendation are based on Tri-Seal's Laboratory Findings and are believed to be true and accurate, but we strongly recommend that our customers perform appropriate tests they feel necessary to ensure the compatibility and stability of any given product with ours. Tri-Seal, a Tekni-Plex Co. guarantees to replace any quantity proved to be defective. We will not be held liable for any injury, loss or change, whether direct, incidental or consequential, due to the use of or inability to use the product due to a breach of warranty of any agreement between Tri-Seal and the purchaser. Unless contained in this data sheet or agreed to in writing by the officers of the seller and user no other warranty will be honored.